



Degreasing Solution

Product Features

Description

F2 Eco Degreasing Solution (Concentrate) is a high-strength, caustic-free, aluminium-safe cleaner formulated for vessel hulls, propellers, and marine equipment. It rapidly removes oil, grease, fuel film, and stubborn residues without harsh chemicals or solvents.

Environmental Profile

Contains surfactants that meet the biodegradability criteria of Regulation (EC) No. 648/2004 (Detergents Regulation). Designed for minimal impact on marine environments when used as directed and may be used in areas where conventional detergents are restricted.

All-round performance

- Concentrate for flexible dilution and economy
- Caustic-free & solvent-free formulation
- Aluminium safe; compatible with common marine substrates
- Effective on oil, grease, and heavy residues
- Suitable for use with hot or cold water.

Composition

A complex blend of surfactants

Product Safety

Safety Precautions

Application should be carried out in accordance with the instructions on this data sheet, the safety data sheet, and the container labels. National occupational health and safety regulations must be observed.

Product Data

Color

Clear liquid

pH

Neutral

Density

1.085 g/cm³

Available Packaging

1L



Ocean Coatings
HIGH PERFORMANCE COATINGS



Degreasing Solution

Application

Dilution

Normal degreasing	1:10
Heavy contamination	1:4

Application

- Apply with a brush or sponge. Agitate with a brush to lift residues.
- Allow to work for ~2 minutes; do not let dry on the surface.
- Thoroughly rinse with fresh water. Repeat if necessary.

Application Notes

- Works with hot or cold water; aluminium-safe on sound coatings. Always test a small area first. Wear suitable PPE. Do not mix with other cleaners.
- In hot weather we recommend surfaces to be presprayed with cold water before application of cleaning solution

Disposal

Excess material and empty containers must be disposed of in accordance with regulations.

Storage

Storage Conditions

Store cool and dry (5-10°C).

Shelf Life

Unopened containers: 24 months.

The information given in this sheet is not intended to be exhaustive and any person using the product other than that specifically recommended in this sheet does so at their own risk. Any warranty, if given, is contained within Ocean Coatings Ltd Terms and Conditions of sale. Whilst we endeavour all advice given about the product is correct we have no control over either the quality or condition of the substrate or other factors affecting the use of the product. Therefore we do not accept any liability whatsoever or however arising for the performance of the product or for any loss or damage arising out of use of the product.

Ocean Coatings Ltd

NetPark Plexus, Sedgfield, Co Durham TS21 3FD, UK

TEL: +4433 3344 1760, MAIL: info@ocean-coatings.com

