



Product Features

Description

F2 EcoWash (Rejuvenator) is a ready-to-use wash and surface refresher formulated for the F2 EcoHull Top Coat. It removes salt, grime, and light biofilm while rejuvenating the hydrophobic beading to keep the surface smooth, clean, and low-friction. Ideal at haul-out. Designed to be gentle on the F2 coating while restoring easy-clean performance.

Environmental Profile

Contains surfactants that meet the biodegradability criteria of Regulation (EC) No. 648/2004 (Detergents Regulation). Designed for minimal impact on marine environments when used as directed and may be used in areas where conventional detergents are restricted.

All-round performance

- Clean & refresh in one step—removes residues and restores water-repellency
- Coating-safe—maintains the F2 EcoHull Top Coat's glide and appearance
- Suitable for routine washdowns and haul-out cleaning

Composition

A complex blend of surfactants

Product Safety

Safety Precautions

Application should be carried out in accordance with the instructions on this data sheet, the safety data sheet, and the container labels. National occupational health and safety regulations must be observed.

Product Data

Color

Clear liquid

pH

Neutral

Density

1.085 g/cm³

Available Packaging

1L



Ocean Coatings
HIGH PERFORMANCE COATINGS



Application

Application

- Method (rejuvenation at maintenance lift): Apply neat/undiluted using a foam lance to create a thick foam blanket.
- Agitation: Work the surface with a soft brush to lift residues.
- Dwell time: Allow to act for ~2 minutes; do not let the product dry on the surface.
- Rinse: Thoroughly rinse with fresh water.

Application Notes

- Hot-weather guidance: On warm or windy days, pre-wet surfaces with cold water before application to prevent premature drying.
- Notes: Suitable for use on F2 EcoHull Top Coat and adjacent marine substrates when used as directed. Test a small area first. Wear appropriate PPE. Do not mix with other cleaners.

Disposal

Excess material and empty containers must be disposed of in accordance with regulations.

Storage

Storage Conditions

Store cool and dry (5-10°C).

Shelf Life

Unopened containers: 24 months.

The information given in this sheet is not intended to be exhaustive and any person using the product other than that specifically recommended in this sheet does so at their own risk. Any warranty, if given, is contained within Ocean Coatings Ltd Terms and Conditions of sale. Whilst we endeavour all advice given about the product is correct we have no control over either the quality or condition of the substrate or other factors affecting the use of the product. Therefore we do not accept any liability whatsoever or however arising for the performance of the product or for any loss or damage arising out of use of the product.

Ocean Coatings Ltd

NetPark Plexus, Sedgfield, Co Durham TS21 3FD, UK

TEL: +4433 3344 1760, MAIL: info@ocean-coatings.com

